


How does it work?



- 1 Fresh outside air**
is drawn in via a fan.
- 2 Filtered air**
is cleaned by high efficiency air filters.
- 3 Heat & mass exchange**
Air enters newly patented HMXs.
- 4 Working air & water**
50% of air entering is saturated with water & returns to atmosphere carrying heat energy removed from the conditioned air.
- 5 Conditioned air**
Balance of air that enters HMX is cooled without adding humidity.

C60 Air Conditioner

Features and specifications

- Patented heat & mass exchange (HMX) technology
- Super-versatile casing that's stackable side-by-side
- Increases cooling power with ease
- Durable, easy to install & maintain
- Low profile design
- Can significantly reduce your energy bills
- Can increase your LEED credits
- Ideal for data centers, health care facilities, retail stores restaurants & other applications



Return on investment

- Up to 80% less energy than conventional systems
- Quick investment payback
- Low total cost of ownership

Sustainable

- No chemical refrigerants
- Improves indoor air quality
- Best alternative for sustainable/LEED projects

Third-party verified



Conditioned air

- Flow at 1,350 CFM [635 L/s] without ducting losses
- Intake airflow at 2,349 CFM [1105 L/s]
- Working airflow at 999 CFM [470 L/s]
- Cooled to approx. 95 to 120% of intake air's wet bulb temperature without changing moisture content

Another quality product by



Specifications


- EER* 100+
- COP^ 29.3+
- Cooling capacity & efficiency increases as temperature increases
- 100% outdoor, filtered air
- No chemical refrigerants or compressor
- No moisture added to conditioned air
- Low maintenance & water use
- New, patented Maisotsenko thermodynamic cycle
- 3 year limited warranty
- Easy to install, no assembly needed
- Stackable for transportation and warehouse space saving

*Energy Efficiency Ratio. ^Coefficient of Performance.



**Unique design
& performance
features**

1. ABS plastic drain pan, frame & internal components that directly contact water. Powder coated electrogalvanized steel housing.
2. Front access integrated electrical panel & control system.
3. Tapered intake plenum increases fan efficiency & evens air distribution.
4. No tool air filters access panel - 4 standard size 20" (508mm) x 25" (635mm) x 2" (50.8mm) MERV 8 ring frame air filters.
5. Discharge plenum provided for easy ducting by cutting any size or shape hole into the plenum face.
6. Side panel can be used for ducting exhaust or optional louver.
7. High efficient, variable speed, electronically commutated motorized (ECM) fan.
8. Zero side clearance - modular, multiple unit configurations.



Options

- A. Thermostat auto-variable motor speed control
- B. Manual-variable motor speed control
- C. Exhaust Louvers
- D. Insulated Plenum
- E. 120V, 60Hz, 1250 Watt AC motor (does not work with options A or B)

Another quality product by



coolerado.com